

SMART BATTERY CHARGER

12V 12A - 24V 6A



MCU Control



TEMP DETECTION



REPAIR MODE



FULL PROTECT



FAST CHARGE



AUTO MEMORY

7-STAGE CHARGING PROCESS

7-stage charging process, more friendly to battery charging.



1-STAGE: Battery desulphation

2-STAGE: Soft start charging

3-STAGE: Bulk charging

4-STAGE: Absorption charging

5-STAGE: Battery test

6-STAGE: Recondition charging

7-STAGE: Float & maintenance charging





Microprocessorbesturing (CPU).

7-FASEN AUTOMATISCH LADEN

- Dit is een volautomatische acculader met 7 laadfasen.
- Automatisch laden beschermt uw accu tegen overladen. U kunt de lader daarom onbeperkt op de accu aangesloten laten.
- 7-fasenladers zijn geschikt voor de meeste accutypes, waaronder calcium-, gel-/AGM-, LiFePO4-, natte en loodzuuraccu's. Ze kunnen ook helpen om lege en gesulfateerde accu's te herstellen.
- Accutypes: de meeste soorten loodzuuraccu's, waaronder calcium, gel/AGM, LiFePO4, nat, loodzuur, enz.
- Switchmode-technologie (schakelende voeding): Ja
- Ompolingsbeveiliging: Ja
- Kortsluitbeveiliging uitgang: Ja
- Beveiliging tegen laden zonder aangesloten accu: Ja
- Overspanningsbeveiliging: Ja
- Oververhittingsbeveiliging: Ja
- Koeling: ventilator
- Ingangsspanning: 100-240 V AC, 50-60 Hz
- Nominale uitgang: 12 V 12 A, 24 V 6 A
- Minimale startspanning: 8,0 V
- Accucapaciteit: 6-200 Ah
- Thermische beveiliging: 65 °C ± 5 °C
- Rendement: ca. 85%
- Voldoet aan de normen: CE, RoHS, FCC
- Afmetingen (L × B × H): 185 × 118 × 70 mm
- Gewicht: 735 g